



89504 Paired - Computer Cable for EIA RS-232 Applications



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

24 AWG stranded (7x32) tinned copper conductors, plenum, FEP insulation, twisted pair, overall Beldfoil shield (100% coverage), 24 AWG stranded TC drain wire, FEP jacket

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	7x32
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	FEP - Fluorinated Ethylene Propylene
Nom. Insulation Wall Thickness	.006 in.
Lay Length	1.0 in.

Pair Color Code Chart :

Number	Color	Number	Color
1	Black & White	3	Black & Green
2	Black & Red	4	Black & Blue

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	24
Outer Shield Drain Wire Stranding	7x32
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	FEP - Fluorinated Ethylene Propylene
Outer Jacket Nominal Wall Thickness	.014 in.



89504 Paired - Computer Cable for EIA RS-232 Applications

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.192 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-70°C To +200°C
Bulk Cable Weight	26.3 lbs/1000 ft.
Max. Recommended Pulling Tension	50 lbs.
Min. Bend Radius (Install)	1.9 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMP
CEC/C(UL) Specification	CMP
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

FLAME TEST:

UL Flame Test	NFPA 262
C(UL) Flame Test	FT6

PLENUM/NON-PLENUM:

Plenum (Y/N)	Y
Non-Plenum Number	9504

ELECTRICAL CHARACTERISTICS:

Nom. Inductance	.17 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	21 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	40 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	24.1 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	15.9 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	1.5 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
89504 0021000	4 SH PR #24 FEP FEP	1000	29	RED	C
89504 002500	4 SH PR #24 FEP FEP	500	14.5	RED	C

C = CRATE REEL PUT-UP.



89504 Paired - Computer Cable for EIA RS-232 Applications

Revision Number: 1 Revision Date: 07-26-2005

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.